

# TOYOTOMI

## CONVECTION TYPE KEROSENE HEATER Model KS-R25

### FEATURES

#### ■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

#### ■ DURABLE GLASS FIBER WICK

Durable Glass Fiber Wick ensures a longer wick life-time than the cotton wick.

#### ■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on KS-R25.

1. Retracting the wick manually by the Main Knob:  
Reducing odor by long extinguishment (1 - 5 min.).
2. Simple touch of a Shut-off button:  
Extinguishment in short time (less than 10 sec.).
3. Automatic shut-off is activated when the heater is bumped or tips over: Safety system for earthquakes.

#### ■ SPARK IGNITION SYSTEM

This new uniquely designed spark ignition system is maintenance free and avoids any troubles caused by broken igniter coils, often found in conventional ignition system.

#### ■ DOUBLE WALL TANK STRUCTURE

The double wall tank structure prevents fuel leakage even when heater tips over for safety.

#### ■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



### SPECIFICATIONS

<b>PRODUCT DESIGNATION NO.:</b>	KS-R25
<b>HEATING CAPACITY:</b>	8,600 BTU/h (2.54 kW)
<b>FUEL CONSUMPTION:</b>	0.247 L/h
<b>TANK CAPACITY:</b>	6.0 L
<b>BURNING TIME:</b>	Approx. 24 hrs.
<b>HEATER DIMENSIONS (WxDxH):</b>	388 x 388 x 474.5 mm
<b>ACCESSORIES:</b>	Manual Fuel Syphon Pump, Batteries (Type C x 4 pcs.)
<b>CARTON DIMENSIONS (WxDxH):</b>	420 x 420 x 510 mm
<b>NET / GROSS WEIGHT:</b>	Approx. 5.9 / 7.5 kg
<b>CONTAINER Q'TY (20 / 40 / 40HC):</b>	323 / 655 / 756 units

#### TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,  
NAGOYA, 467-0855 JAPAN  
TEL : 81-52-822-1108, FAX : 81-52-824-7151  
E-mail: [ftd@toyotomi.jp](mailto:ftd@toyotomi.jp)  
Website: [www.toyotomi.jp](http://www.toyotomi.jp)

Printed in Japan

Subject to change with or without notice