

Split Air Conditioner

KURO series

FEATURES



SPECIFICATIONS

MODEL	INDOOR	TKN-628R32	TKN-635R32	TKN-656R32	TKN-671R32
	OUTDOOR	TKG-628R32	TKG-635R32	TKG-656R32	TKG-671R32
COOLING CAPACITY		8,900 BTU (2.61 kW)	12,000 BTU (3.52 kW)	18,000 BTU (5.28 kW)	24,000 BTU (7.03 kW)
HEATING CAPACITY		10,000 BTU (2.93 kW)	13,000 BTU (3.81 kW)	19,000 BTU (5.57 kW)	24,800 BTU (7.62 kW)
COOLING	SEER	8.5	8.5	7.6	7.0
	COOLING ENERGY CLASS	A+++	A+++	A++	A++
HEATING	SCOP AVERAGE ZONE	4.6	4.4	4.1	4.0
	ENERGY CLASS AVERAGE ZONE	A++	A+	A+	A+
	SCOP WARMER ZONE	5.4	5.1	5.2	5.2
	ENERGY CLASS WARMER ZONE	A+++	A+++	A+++	A+++
POWER SOURCE		220-240V, 50Hz			
DEHUMIDIFYING CAPACITY		1.4 L / h	1.4 L / h	1.8 L / h	2.4 L / h
COMPRESSOR		Rotary			
REFRIGERANT		R32			
DIMENSIONS (W x H x D)	INDOOR	928x364x278	928x364x278	1057x377x307	1164x402x339
	OUTDOOR	878x630x360	878x630x360	1026x735x455	1026x735x455
WEIGHT	INDOOR	12.5	13	16.5	20
	OUTDOOR	36.5	36.5	49.5	57.5
FEATURES		Meets the current European ErP directive, Higher energy efficiency, Smart Wi-fi, I-FEEL function, 8°C heating			

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB170081 New: 03/17
Subject to change with or without notice