

Laser Clean Wickless Fan Heater

Model LC-44

FEATURES

■ WICKLESS DESIGN

Provides clean and economical heat without wick maintenance or replacement.

■ SEMI-AUTOMATIC OPERATION

Features a 24-hour programmable timer and an integrated thermostat controller to maintain the desired room temperature. It offers 5 cycle burning mode (High ⇄ Med.-High ⇄ Med. ⇄ Med.-Low ⇄ Low).

■ SAVE MODE

In addition to 5 cycle burning mode, burning stop operation is available not to overheat the room.

■ COOL TOP CABINET

Prevents accidental contact burns.

■ BUILT-IN FAN

Circulates clean, even warmth throughout the room.

■ SAFETY DEVICE

The heater is equipped with a Tip-over Switch, Ignition Safety Device, Burning Control Device, Safety Device for Power Outage, High Limit Switch (Overheat Protector), Incomplete Combustion Preventive Device (Flame Rod, Burner Thermistor)

■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



SPECIFICATIONS

MODEL:	LC-44
TYPE OF HEATER:	Laser Clean Wickless Fan Heater (forced convection type)
HEATING RATING:	High: 14,300 BTU/h (4.20 kW/h) – Low: 3,800 BTU/h (1.10 kW/h)
FUEL CONSUMPTION:	High: 0.406 L/h – Low: 0.109 L/h
POWER SOURCE:	AC 230 V / 50 Hz
ELECTRICAL CONSUMPTION:	Igniter: 320 W – Continuous: 25 W
TYPE OF FUEL:	Kerosene
TANK CAPACITY:	7.6 L
BURNING TIME:	Approx. 19.0 – 69.0 hrs.
HEATER DIMENSIONS (WxDxH):	435 x 315 x 437 mm
CARTON DIMENSIONS (WxDxH):	475 x 355 x 480 mm
NET / GROSS WEIGHT:	Approx. 11.5 / 13.5 kg
CONTAINER Q'TY (20 / 40 / 40HC):	304 / 632 / 790 units

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
 NAGOYA, 467-0855 JAPAN
 TEL : 81-52-822-1108, FAX : 81-52-824-7151
 E-mail: ftd@toyotomi.jp
 Website: www.toyotomi.jp

Printed in Japan

Subject to change with or without notice