

Split Air Conditioner

NOBORU series

FEATURES



SPECIFICATIONS

MODEL	INDOOR	NTN-928R32	NTN-935R32	NTN-956R32	NTN-971R32
	OUTDOOR	NTG-928R32	NTG-935R32	NTG-956R32	NTG-971R32
COOLING CAPACITY		9,042 BTU (2.65 kW)	12,113 BTU (3.55 kW)	18,084 BTU (5.30 kW)	24,225 BTU (7.10 kW)
HEATING CAPACITY		9,895 BTU (2.90 kW)	12,283 BTU (3.60 kW)	19,107 BTU (5.60 kW)	24,225 BTU (7.10 kW)
POWER SOURCE		220-240V, 50Hz			
COOLING	SEER	6.1	6.1	6.5	6.4
	COOLING ENERGY CLASS	A++	A++	A++	A++
HEATING	SCOP AVERAGE ZONE	4.1	4.1	4.1	4.3
	ENERGY CLASS AVERAGE ZONE	A+	A+	A+	A+
	SCOP WARMER ZONE	5.2	5.3	5.4	5.4
	ENERGY CLASS WARMER ZONE	A+++	A+++	A+++	A+++
DEHUMIDIFYING CAPACITY		1.4 L / h	1.4 L / h	1.8 L / h	2.4 L / h
COMPRESSOR		Rotary			
REFRIGERANT		R32			
DIMENSIONS (W x H x D)	INDOOR	850x370x270	850x370x270	1041x385x317	1160x400x305
	OUTDOOR	850x620x370	850x620x370	920x620x400	1020x770x430
WEIGHT	INDOOR	10.5	10.5	14.0	17.0
	OUTDOOR	29.0	29.0	39.0	49.0
FEATURES		Meets the current European ErP directive, Higher energy efficiency, Self clean function, Autorestart, Intelligent defrost			

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN

TEL: +81-52-822-1108

FAX: +81-52-824-7151

E-mail: ftd@toyotomi.jp

Website: www.toyotomi.jp

#TB200127 New: 08/20

Subject to change with or without notice