

Wick Type Kerosene Heater

Model OMNI 230

FEATURES

- **CLEAN COMBUSTION SYSTEM**
 The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unnecessary emission gases to very safety level.
- **TRIPLE SAFETY EXTINGUISHER**
 There are 3 extinguishing methods on OMNI 230.

 1. By retracting the wick
 2. By a simple touch of a lever
 3. Automatic shut-off is activated when the heater is bumped or in the event of a tip-over.
- **WICK LIFE EXTENDER**
 TOYOTOMI's own patented wick height adjustable design can give you longer wick life and better performance.
- **HIGH EFFICIENCY**
 The TOYOTOMI heater has 99.99% heat efficiency with Infrared-Ray heating.
- **DOUBLE WALL TANK CONSTRUCTION**
 The Double Wall Tank Construction prevents leakage even when heater tips over for safety.
- **Spark ignition system ignites the wick by discharging electricity between two electrodes, by simply just giving the main knob (for wick adjuster) a full turn to the right. This new uniquely designed spark ignition system is maintenance free.**



SPECIFICATIONS

| | |
|---|---------------------------|
| MODEL: | OMNI 230 |
| TYPE OF HEATER: | Wick Type Kerosene Heater |
| HEATING CAPACITY: | 23,000 BTU/h (6.77 kW/h) |
| FUEL CONSUMPTION: | 0.659 L/h |
| TYPE OF FUEL: | Kerosene only |
| FUEL TANK CAPACITY: | 7.5 L |
| BURNING TIME: | 12 - 16 hours |
| HEATER DIMENSIONS (WxDxH): | 440 x 440 x 583 mm |
| WEIGHT: | 10.7 kg |
| CONTAINER Q'TY (20 / 40 / 40HC): | 225 / 475 / 520 units |

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
 Mizuho-ku, Nagoya
 467-0855 JAPAN

TEL: +81-52-822-1108

FAX: +81-52-824-7151

E-mail: ftd@toyotomi.jp

Website: www.toyotomi.jp

#TB130007 Rev. 02/16

Subject to change with or without notice