

Split Air Conditioner

SATORI series

FEATURES



SPECIFICATIONS

MODEL	INDOOR	STN-909R32	STN-912R32	STN-918R32	STN-924R32
	OUTDOOR	STG-909R32	STG-912R32	STG-918R32	STG-924R32
COOLING CAPACITY		8,871 BTU (2.60 kW)	11,942 BTU (3.50 kW)	17,913 BTU (5.25 kW)	23,884 BTU (7.00 kW)
HEATING CAPACITY		9,554 BTU (2.80 kW)	11,942 BTU (3.50 kW)	18,766 BTU (5.50 kW)	23,884 BTU (7.00 kW)
POWER SOURCE		220-240V, 50Hz			
COOLING	SEER	6.1	6.1	6.6	6.9
	COOLING ENERGY CLASS	A++	A++	A++	A++
HEATING	SCOP AVERAGE ZONE	4.1	4.1	4.0	4.1
	ENERGY CLASS AVERAGE ZONE	A+	A+	A+	A+
	SCOP WARMER ZONE	5.4	5.4	5.4	5.2
	ENERGY CLASS WARMER ZONE	A+++	A+++	A+++	A+++
DEHUMIDIFYING CAPACITY		1.4 L / h	1.4 L / h	1.8 L / h	2.4 L / h
COMPRESSOR		Rotary			
REFRIGERANT		R32			
DIMENSIONS (W x H x D)	INDOOR	820x345x265	820x345x265	970x382x302	1155x397x312
	OUTDOOR	850x620x370	850x620x370	920x620x400	1020x770x430
WEIGHT	INDOOR	9.5	10.0	14.0	17.0
	OUTDOOR	29.0	29.0	39.0	49.0
FEATURES		Meets the current European ErP directive, Higher energy efficiency, Self clean function, Autorestart, Intelligent defrost			

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN

TEL: +81-52-822-1108

FAX: +81-52-824-7151

E-mail: ftd@toyotomi.jp

Website: www.toyotomi.jp

#TB200128 New: 08/20

Subject to change with or without notice