

Desiccant Type Dehumidifier Model TD-Z110

TOYOTOMI

FEATURES

■ DESICCANT TYPE DEHUMIDIFIER

This model features desiccant instead of compressor. Accordingly this model is not affected by room temperature and this model can be used all season even if it is wet winter.

■ DEW CONDENSATION PREVENTING MECHANISM

Humidity sensor controls room humidity from 35% to 40% automatically to prevent dew condensation on the wall and window.

■ AUTOMATIC OPERATION

This model is equipped with humidity sensor and room humidity is controlled automatically at 45% - 50%.

■ LAUNDRY DRY MODE

Laundry Dry Mode can make dry speedily the hanged laundry in the room. You can select Turbo Dry Mode or Saving Dry Mode depending on the laundry amount.

■ OFF-TIMER

It has off-timer function which can be selected 2 Hrs., 4 Hrs. or 8 Hrs.

■ AUTO SWING LOUVER

It can be selected 3 way angles, wide angle (150°), front angle (60°), or upward angle (90°).

■ WIDE / SPOT / DOWNWARD LOUVER (MANUAL)

By adjust the manual louver, you can select wide or spot air flow. Downward Louver is suitable for drying bathroom floor etc.



SPECIFICATIONS

MODEL:	TD-Z110
APPLYCABLE SPACE:	45 m ²
DEHUMIDIFYING CAPACITY:	11 L/day (20°C 60%RH)
POWER SOURCE:	AC 230V, 50Hz
OPERATION TEMPARATURE RANGE	1°C – 40°C
OPERATION MODE:	Automatic (High/Low/Auto) Laundry Dry (Turbo/Saving)
POWER COMSUMPTION:	Automatic Mode 400 W
	High Mode 740 W
	Low Mode 400 W
	Laundry Dry Mode
	(Turbo Dry Mode) 740 W
	(Saving Dry Mode) 740 W
NOISE LEVEL:	Automatic Mode 49 dB
	High Mode 49 dB
	Low Mode 35 dB
	Laundry Dry Mode
	(Turbo Dry Mode) 49 dB
	(Saving Dry Mode) 49 dB
TANK CAPACITY:	3.8 L
PRODUCT DIMENSIONS (WxDxH):	462x 217 x 528 mm
WEIGHT:	8.2 kg

TOYOTOMI CO., LTD.
5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp
#TB110001 Rev.: 11/16
Subject to change with or without notice