

Desiccant Type Dehumidifier Model TD-Z80

TOYOTOMI

FEATURES

■ DESICCANT TYPE DEHUMIDIFIER

This model features desiccant instead of compressor. Accordingly this model is not affected by room temperature and this model can be used all season even if it is wet winter.

■ DEW CONDENSATION PREVENTING MECHANISM

Humidity sensor controls room humidity from 35% to 40% automatically to prevent dew condensation on the wall and window.

■ AUTOMATIC OPERATION

This unit is equipped with humidity sensor and room humidity is controlled automatically at 45% - 50%.

■ LAUNDRY DRY MODE

Laundry Dry Mode can make dry speedily the hanged laundry in the room. You can select Turbo Dry Mode or Saving Dry Mode depending on the laundry amount.

■ OFF-TIMER

It has off-timer function which can be selected 2 Hrs., 4 Hrs. or 8 Hrs.

■ AUTO SWING LOUVER

It can be selected 3 way angles, wide angle (150°), front angle (50°), or upward angle (100°).

■ WIDE / SPOT ADJUSTABLE LOUVER (MANUAL)

By adjust the manual louver, you can select wide or spot air flow.



SPECIFICATIONS

MODEL:	TD-Z80	
APPLYCABLE SPACE:	33 m ²	
DEHUMIDIFYING CAPACITY:	8 L/day (20°C 60%RH)	
POWER SOURCE:	AC230V, 50Hz	
OPERATION TEMPARATURE RANGE:	1 °C - 40 °C	
OPERATION MODE:	Automatic Dry (Auto/High /Low), Landry Dry (Turbo/Saving)	
POWER COMSUMPTION:	620W(High)/350W(Low)	
NOISE LEVEL:	Automatic Mode	47 dB
	High Mode	47 dB
	Low Mode	35 dB
	(Turbo Dry Mode)	47 dB
	(Saving Dry Mode)	47 dB
TANK CAPACITY:	2.2 L	
PRODUCT DIMENSIONS (WxDxH):	320 x 212 x 476 mm	
WEIGHT:	6.1 kg	

Laundry Dry Mode

TOYOTOMI CO., LTD.
5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB100072 Rev.: 11/16

Subject to change with or without notice