

Desiccant Type Dehumidifier

Model TD-ZB80

TOYOTOMI

FEATURES

■ DESICCANT TYPE DEHUMIDIFIER

This model features desiccant instead of compressor. Accordingly this model is not affected by room temperature and this model can be used all season even if it is wet winter.

■ DEW CONDENSATION PREVENTING MECHANISM

Humidity sensor controls room humidity from 35% to 40% automatically to prevent dew condensation on the wall and window.

■ AUTOMATIC OPERATION

This unit is equipped with humidity sensor and room humidity is controlled automatically at 45% - 50%.

■ LAUNDRY DRY MODE

Laundry Dry Mode can make dry speedily the hanged laundry in the room. You can select Turbo Dry Mode or Saving Dry Mode depending on the laundry amount.

■ OFF-TIMER

It has off-timer function which can be selected 2 Hrs., 4 Hrs. or 8 Hrs.

■ AUTO SWING LOUVER

It can be selected 3 way angles, wide angle (180°), front angle (80°), or upward angle (100°).

■ WIDE / SPOT ADJUSTABLE LOUVER (MANUAL)

By adjust the manual louver, you can select wide or spot air flow.



SPECIFICATIONS

MODEL:	TD-ZB80
APPLYCABLE SPACE:	33 m ²
DEHUMIDIFYING CAPACITY:	8 L/day (20°C 60%RH)
POWER SOURCE:	AC220-240V, 50Hz
OPERATION TEMPARATURE RANGE:	1 °C - 40 °C
OPERATION MODE:	Automatic Dry (Auto/High /Low), Landry Dry (Turbo/Saving)
POWER COMSUMPTION:	620W(High)/350W(Low)
NOISE LEVEL:	50 dB(High)/34(Low)
TANK CAPACITY:	4.0 L
PRODUCT DIMENSIONS (WxDxH):	350 x 240 x 506 mm
WEIGHT:	7.2 kg

TOYOTOMI CO., LTD.
5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp
#TB100072-2 Rev.: 11/16

Subject to change with or without notice